

INSTRUCTIONS



LED PANEL LIGHT

7835.6060.40.30.31

7835.6060.40.40.31

Please read the instructions before commencing installation and retain for future reference.

SPECIFICATIONS:

- **Fitting:** Body made in aluminium with polystyrene diffuser.
- **Lamp types:**
 - LED 40W Natural White 4000K
7835.6060.40.40.31
 - LED 40W Warm White 3000K
7835.6060.40.30.31
- **Protection against electric shock:** CLASS II.
- **Ingress Protection:** IP20, for indoor use.
- **Ballast:** Includes LED driver.
- **Quality/Corrosive rating:** Suitable for indoor Installation.
- **Ambient temperature range:** -20°C to +60°C.

INSTALLATION INSTRUCTIONS:

⚠ Electrical products can cause death, injury, damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 10142. On completion of installation, ensure that the Certificate of Compliance is updated.

Ensure mains supply is switched off.

- Remove the ceiling panel. (Fig. 1)
PLEASE NOTE: This fitting can be surface mounted or suspended using the accessory codes below:
 - 7835.SUSP: Suspension kit only
 - 7835.FRAME: Surface mount frame
- Connect driver on panel light to its electrical source in accordance to the SANS1042 standard. (Fig 2)
- Place the fitting into the ceiling. (Fig. 3)
- Switch on mains (Fig. 4)

WARNING:

- Ensure all items and screws are secure and fitted correctly.

