# **INSTRUCTIONS**

# RING LED PENDANT DIMMABLE

#### Art. No. 8585.38.30.30.D / 8585.38.30.31.D

Please read the instructions before commencing installation and retain for future reference.

#### SPECIFICATIONS:

- Fitting: Aluminium frame, metal base + silica gel trim
- Lamp types: 38W / 230V / LED 3000K
- Protection against electric shock: CLASS I. Requires earth connection.
- Ingress Protection: IP20. Protection against the entry of solid bodies with dimensions > 12mm
- Driver: Includes LED Driver
- Quality/Corrosive rating: Suitable for indoor commercial and residential applications
- Ambient temperature range: -8°C to +55°C.

### **INSTALLATION INSTRUCTIONS:**

Electrical products can cause death, injury or damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 10142. On completion of installation, ensure that the Certificate of Compliance is updated.



CAUTION: Risk of electric shock

PLEASE NOTE: The light source contained on this luminaire shall only be replaced by the manufacturer or the service agent or a similar qualified person.

### Ensure main supply is switched off.

- Mount two expansion anchors (supplied) on the ceiling. (Fig.1)
- Mount the ceiling bracket to the anchors with the screws provided. (Fig. 2)
- Connect the fitting to its electrical source using the terminal block provided: (Fig. 3)
  Brown (Live) - to Brown or Red Blue (Neutral) - to Blue or Black
  - Green/Yellow (Earth) to Green/Yellow or Copper.
- · Re-attach the fitting base to the ceiling bracket. (Fig. 4)
- Adjust the length of cables as needed. (Fig. 5)

#### Switch main supply back on and test the fitting.

## WARNING:

- Ensure all items and screws are secure and fitted correctly.



