INSTRUCTIONS

NAUGHTY BOLLARD

8598.1.52

Please read the instructions before commencing installation and retain for future reference.

SPECIFICATIONS:

- · Fitting: Aluminum body with polycarbonate diffuser.
- · Lamp types:
 - 6W LED Warm White 3000K (removed OSRAM) 6W LED Natural White 4000K (removed OSRAM)
- Protection against electric shock: CLASS I requires earth connection.
- Ingress Protection: IP54.Protection against dust and water splashes
- · Ballast: Includes LED Driver
- Quality/Corrosive Rating: Suitable for outdoor domestic and commercial applications.
- Ambient temperature range: -20° to +40°

INSTALLATION INSTRUCTIONS:

Electrical products can cause death, injury or damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 10142. On completion of installation, ensure that the Certificate of Compliance is updated.



CAUTION: Risk of electric shock

PLEASE NOTE: The light source contained on this luminaire shall only be replaced by the manufacturer or the service agent or a similar qualified person.

Ensure mains supply is switched off.

- Mark and drill three holes according to the base where you would like to install the fitting. (Fig. 1)
- Insert the plastic expansion screws.
- Pull out the terminal block mount from the fitting and remove the terminal block from it and connect to the mains supply (Fig. 2)

Brown (Live) - to Brown or Red

Blue (Neutral) - to Blue or Black

Green/Yellow (Earth) - to Green/Yellow or Copper.

- Re-attach the terminal block to the mount and re-insert it into the fitting. (Fig. 3)
- Install the fitting on the ground with the screws provided

Switch on mains supply

WARNING

- Ensure all items and screws are secure an fitted correctly



