INSTRUCTIONS

SILK PENDANT

8651.1.500 / 8651.1.750 8651.2.200 / 8651.2.300

8651.3.320 / 8651.3.400 / 8651.3.500

Please read the instructions before commencing installation and retain for future reference.

SPECIFICATIONS:

- Fitting: Metal base and frame with polymer resin shade
- Lamp types: Max. 60W / E27
- Protection against electric shock: CLASS I. Requires earth connection.
- **Ingress Protection:** IP20.
- Quality/Corrosive rating: Suitable for indoor commercial and residential applications.
- Ambient temperature range: -8°C to +55°C.

INSTALLATION INSTRUCTIONS:

A Electrical products can cause death, injury or damage to property. Installation of this product must be carried out by a qualified electrician, in accordance with SANS 10142. On completion of installation, ensure that the Certificate of Compliance is updated.

Ensure main supply is switched off.

- Mount the two expansion anchors (supplied) on the ceiling. (Fig. 1)
- Mount the ceiling bracket to the anchors with the screws provided. (Fig. 2)
- Connect the fitting to its electrical source using the terminal block provided. (Fig. 3) Brown (Live) - to Brown or Red

Blue (Neutral) - to Blue or Black

Green/Yellow (Earth) - to Green/Yellow or Copper.

- Fix the fitting base to the ceiling bracket. (Fig. 4)
- Adjust the length of suspension cable as needed. (Fig. 5)
- Install the lamp. (Fig. 6)

Switch main supply back on and test the fitting.

WARNING:

- Ensure all items and screws are secure and fitted correctly.





