D-15 MINI MOBILE AIR COMPRESSOR

Optional

Directly Coupled - SKF Bearings

Internal, force cooled

12



MODEL		
FILTER RACK		
AIR END		
AFTER-COOLER		
BATTERY	(v)	
START SYSTEM		
THROTTLE CONTROL		
LOAD CONTROL		
ENGINE MONITORING SYSTEM		
CAPACITY	(M³/MIN) / (CFM)	
PRESSURE	BAR/MPA	
DIMENSION	(MM)	
WEIGHT	(KG)	
COOLING METHOD		
DRIVE TYPE		
OUTLET AIR TEMPERATURE	(°C)	
COMPRESSION STAGE		
NOISE LEVEL [dB(A)]	[dB(A)]	
OUTLET		
SPEED AT FULL LOAD	(RPM)	
FUEL TANK CAPACITY	(L)	
PETROL ENGINE BRAND		
MODEL		
V POWER	(KW)	

	Electric, with key start
	Manual
	Manual
	Mebay GM50H Digital - Oil Pressure, Temperature, Voltage, Hour Meter
	1,15 / 40,6
١.	12,5 / 1,25
	1200Lx750Wx1180H with wheels fitted
	220
	Air Cooled
	Directly Coupled and Driven
	≤10~15 (+ ambient temp.)
	Single
_	≤97
	G 1/2"
_	3650
_	25
_	Honda Powered
	GX-690
	14 (Max. power 17)













