**PRODUCT DATA SHEET** 



# BAROCEL 7045 CAPACITANCE DIAPHRAGM GAUGE

edwardsvacuum.com

# The Barocel 7045 heated capacitance gauge gives the greatest accuracy in the harshest environments.

With a fast heat up (to a constant 45°C) and a surface that is safe to touch, these are the most advanced capacitive gauges available on the market. Utilising the corrosion resistant ceramic sensing cell (with total alumina coating) found across the 7000 series along with the integrated baffle and sensor protection these sensors are truly fit and forget.




#### Features and benefits

- 0.1 to 1000 torr variants
- Fast reaction time
- · Corrosion resistant sensor
- Zero maintenance
- Fantastic zero and full scale stability
- Temperature compensated

### **Typical applications**

- High temperature coating
- Dry etch
- Sterilization
- General high temperature vacuum applications
- Oxidation
- CVD/PVD/etch
- Industrial

#### Barocel 7045 selection tree



PRODUCT DATA SHEET edwardsvacuum.com

#### Technical data

Performance	7045		
FS options	1000(1100)	100/10/1	0.1
Accuracy (% of reading)	0.15	0.15	0.15
Temperature effect			
On zero (percentage FS/°C)	0.0025	0.0025	0.005
On span (% of reading/°C)	0.01	0.01	0.01
Resolution (percent FS)	0.003	0.003	0.003
Lowest reading (percent FS)	0.05	0.05	0.05
Admissible temps			
Ambient(°C)	+10 to + 40	+10 to + 40	+10 to +40
Bakeout (at flange) (°C)	<110	<110	<110
Storage (°C)	-20 to +65	-20 to +65	-20 to +65
Pressure max (kPa) absolute	400	260	130
Supply voltage V (dc)	+14 to +30 or +-15V	+14 to +30 or +-15V	+14 to +30 or +-15V
Power consumption during heat up (W)	<12	<12	<12
Power consumption at operating temperature (W)	<8	<8	<8
Output signal V (dc)	0 to +10	0 to +10	0 to +10
Response time (ms)	30	30	30
IP rating	40	40	40
Dimensions (NW16 & D-sub 15pin)	82x82x142	82x82x142	82x82x142
Materials exposed to vacuum	Aluminium oxide ceramic (AI2O3), stainless steel (AISI 316L)		
Set points			
Number of	2	2	2
Relay contact (V (dc))	30	30	30
Hysterisis (percent F.S)	1	1	1

## Ordering information

Accessory	Order number
TIC instrument controller 6 head capman	D39702000
TIC adaptor cable for Barocel	D40003050

Connection cable options	Order number
0.5 m	D40001005
1 m	D40001010
3 m	D40001030
5 m	D40001050
10 m	D40001100
15 m	D40001150
25 m	D40001250
50 m	D40001500

#### Publication No 3601 0539 01

© Edwards Limited 2019. All rights reserved Edwards and the Edwards logo are trademarks of Edwards Limited.

Whilst we make every effort to ensure that we accurately describe our products and services, we give no guarantee as to the accuracy or completeness of any information provided in this datasheet.

Edwards Ltd, registered in England and Wales No. 6124750, registered office: Innovation Drive, Burgess Hill, West Sussex, RH15 9TW, UK.

# GLOBAL CONTACTS

EMEA		ASIA PACIFIC	
UK	+44 (0) 1444 253 000 (local rate) 0845 921 2223	China	+86 400 111 9618
Belgium	+32 2 300 0730	India Japan	+91 20 4075 2222 +81 47 458 8836
France	+33 1 4121 1256	Korea	+82 31 716 7070
Germany	0800 000 1456	Singapore	+65 6546 8408
Italy	+ 39 02 48 4471	Taiwan	+886 3758 1000
Israel	+ 972 8 681 0633		
		AMERICAS	
		USA	+1 800 848 9800
		Brazil	+55 11 3952 5000

