



FEATURES

- Large digital LCD display clearly indicates the current CO2 level and temperature.
- Easy to read display with all functions set from 3 push buttons.
- Power, upper limit, lower limit and photo sensor verification LEDs.
- Non-UV emitting LEDs means no interference with the grow cycle.
- IP54 Enclosure cover during cleaning and washdown

SPECIFICATIONS

- Measurement Range: 0-10,000 ppm
- Sensing Method: NDIR
- Accuracy: ± 70ppm or ± 5% CO2
- Sensor Response Time: < 2 minutes
- Operating Temperature: 0°-50° C
- Calibration: With fresh air (400 ppm)
- Sensor Life Expectnacy: 15 years
- Max Coverage Area: 140M^2 with proper air handling

ELECTRICAL

- Power Supply: 220-240VAC
- Power Consumption: 2 Watts
- Piggyback Power Cord: CEE 7/3 socket, CEE 7/4 plug
- Piggyback Adapter: Peak Current
 5A @ 250 VAC
- One Relay Output:
 - Peak Current < 5A @ 250 VAC, SPST.
 - Normally Open

ADDITIONAL

- PRT-0346 CO2 Tank Regulator with Solenoid Valve
- RAD-0501A CO2 Controller for Mushroom Farms & Growers
- RAD-0501E Day Night CO2 Monitor & Controller for Greenhouses - US Model

INDUSTRIES



The Day Night CO2 Monitor and Grow Controller is used for tomatoes, lettuce, flowers, cannabis, and angriculture applications.

TYPICAL INSTALLATION

