

# CM-510

## MULTI GAS (CO<sub>2</sub>, CO, O<sub>2</sub>, NH<sub>3</sub>) HANDHELD DETECTOR

#### Handheld Multi Gas Detector

The GasLab Plus CM-510 is a Multi-Gas Meter designed to measure multiple gas concentrations in a wide range of industries and applications.

With long-term data storage, the user can measure ambient gas levels by data displayed and gain indication by visual and audible alarm settings.

#### Features

- NDIR (CO<sub>2</sub>), EC (CO and NH<sub>3</sub>), and Fluorescence quenching by Oxygen (O<sub>2</sub>)
- CO<sub>2</sub>, CO, O<sub>2</sub>, NH3, PM<sub>2.5</sub>, PM<sub>10</sub>, Temp, RH, Baro
- Large LCD display for easy readability
- Audible Alarm
- Data Logging with SD Card
- Multiple Connected Units by RS485 interface
- LCD Backlight for easy readability by dark
- Li-ion rechargeable batteries

#### Accessories

#### BAT-18650 - EBL 18650 3.7V Li-ion

**Rechargeable Batteries** I EBL Intelligent Batteries (need 3 for device) provides a fast charge and are upgraded ETL certified to be used with all CM-500 series handheld gas detectors.

#### EBL Universal Battery Charger for 3.7V

**Rechargeable Batteries** I With the EBL Universal Battery Charger, users will be able to charge the lithium batteries when plugged into a USB outlet. The battery charger also provides a clear indication of charge levels, turning green after fully charged.



## **TECHNICAL DATA**

### Multi Gas $(CO_2, CO, O_2, NH_3)$ Handheld Detector

CO <sub>2</sub> Measurement Range	0~9999 ppm
CO <sub>2</sub> Measurement	NDIR, EC, and Fluorescence quenching by Oxygen
CO Measurement	0~1,000 ppm
O2 Measurement	0-25%
NH <sub>3</sub> Measurement	Performance indicator only
CO <sub>2</sub> Accuracy	± 50ppm, ± 5% of reading (0~5,000 ppm)
CO Accuracy	±5%~±10%
O <sub>2</sub> Accuracy	<2% FS/0.1 mbar
NH <sub>3</sub> Accuracy	±10%
Temperature Range	0~50°C
Sensor Life Expectancy	NDIR: Up to 15 years EC: 1 year NH3: 2 years Fluorescence-based by quenching: 5 years

### Electrical and Mechanical Specifications

Power Supply	Rechargeable Battery : Li-ion 18650 3.7V (device uses 3) AC Adapter : 5V±5% >1A, 100~240 VAC, 50/60 Hz
Battery Life	Tested to 24+ hours



Call 1.877.678.4259 Email Sales@CO2Meter.com | Support@CO2Meter.com Web CO2Meter.com Let's Get Social – @CO2Meter on:

