



MULTI GAS SAFETY SYSTEM O2 SENSOR

Reaching New Heights

The oxygen sensor is the newest addition to the CM-7000 Series Multi Sensor Safety System, now making it possible to sense not only carbon dioxide, but now oxygen in real time.

Features

- Compliant with O2 Safety Standards
- Multiple Sensors per Tablet
- Custom Configurable Options
- LTE Options - Coming Soon!

Works With:

- **CM-7002** | Remote Relay Key Switch
- **CBL-7002** | Relay Cable for CM-7002
- **CM-7003** | Sensor Unit Add On
- **CM-7004** | Horn Strobe Add On
- **CM-7005** | Main Tablet Only
- **CM-7006** | Mini Remote Display Tablet
- **CM-7009** | POE Booster
- **CM-1026-5,6** | CO₂ Storage Safety Strobe Tower
- **SV-1029** | Solenoid Shut-off Valve

Applications



**Breweries
& Wineries**



Pharmaceuticals



Cryogenics



Safety



Agriculture



Medical

TECHNICAL DATA

Multi Gas Safety System O₂ Sensor

Measuring Gas	Oxygen (O ₂)
O₂ Measurement Range	0-23% O ₂
O₂ Measurement	Zirconia
Alarms	20%, 19%, 17%, and 15% (Customizeable)
Display Resolution	0.1%
Operating Temperature	-58-122° F (-50-50° C)
Accuracy	Better than 2% FS
Response Time	<2 minutes by 90%
Warm-Up Time	10 Seconds
Lifetime of Sensor:	10 years

Electrical and Mechanical Specifications

Power Supply	POE via CM-7000 System
Power Input	POE via CM-7000 System
Power Consumption	n/a
4-20mA outputs	0-25% O ₂ Scaled
Mounting Height	Variable by application 12-72inch from the ground



Call 1.877.678.4259
Email Sales@CO2Meter.com | Support@CO2Meter.com
Web CO2Meter.com

Let's Get Social – @CO2Meter on:

