

# RAD-0102-6



# REMOTE CO2 STORAGE SAFETY 3 ALARM

## Our #1 CO, Safety Device

The Remote  $CO_2$  Storage Safety 3 Alarm detects carbon dioxide  $(CO_2)$  levels in ambient air. This protects employees and guests from potentially hazardous gas concentrations. The RAD-0102-6 features audible and visual alarms that can trigger three individual relays. These relays can trigger third-party devices like exhaust systems and fire panels. Ensure the safety of your employees and guests as well as the compliance of your facility with the  $CO_2$  Storage Safety 3 Alarm.

#### **Features**

- · 3 alarms/relays
- · Meets NFPA, IFC, and NBIC requirements
- Meets OSHA and NIOSH TWA standards
- IP54 Enclosure
- UL listed for compliance
- OL listed for compliance
- · Relays can automatically control ventilation fans or signal a fire alarm panel
- LCD display clearly indicates current CO<sub>2</sub> level in ppm or % and temperature

#### Accessories

- CM-1027 | Dual Strobe Add-On Kit
- RAD-0104 | Additional Remote Display
- CM-1026-6 | CO, Storage Safety Strobe Tower
- SV-1029 | Solenoid Shut-off Valve 3/8"
- SV-1030 | Solenoid Shut-off Valve 1/2"



# **TECHNICAL DATA**

# Remote CO, Storage Safety 3 Alarm

CO <sub>2</sub> Measurement Range	0-5% (0-50,000 ppm)
CO <sub>2</sub> Measurement	NDIR (Non-dispersive Infrared)
Alarms	5,000 ppm TWA, 5,000 ppm, 3% (user configurable)
Measurement Interval	2 seconds (0.5 Hz)
Operating Temperature	32-122° F (0-50° C)
Calibration	Zero with Nitrogen or Factory Calibration
Connections	Standard RJ45
Sensor Life Expectancy	>15 years

## **Electrical and Mechanical Specifications**

Power Supply	100-240 VAC 50/60 Hz to 12 VDC power adapter
Power Input	4.5-5.25 VDC
Power Consumption	3 Watts
Hard-Wired	24 VDC hard-wired option (cable included)
Output	4-20 mA

## Alarms & Relays

Response Time	<60 seconds
Alarm Level	88 dB
Relay Power	Peak current <2A @ 30 VDC or 250 VAC, SPDT
Relay Color Coding	Red & White: Normally Open, Blue & White: Normally Closed







Let's Get Social — @CO2Meter on:

