

**UL SOLID UL PC 3819 13 T**



Sample photo

**Order symbol:** UL PC 3819 13 T  
**Product nbr:** 5320061  
**Description:** UL Enclosure, PC  
**Remarks:** Transparent cover

**EAN:** 6418074037510  
**EI. number:**  
**Finland:**  
**Electric No. Denmark:** 8212033142  
**Electric No. Italy:** 7402030U

Including: Base with screws for mounting plate, cover with PUR gasket and polyamide cover screws.

Dimensions:				Rating:
	Length	Width	Height	
<b>mm:</b>	378	188	130	Ingress Protection (EN 60529): IP66/IP67
<b>inch:</b>	14.9	7.4	5.1	Impact Resistance (EN 62262): IK08
Materials:				Electrical insulation: Totally insulated
<b>Material:</b>	Polycarbonate			Halogen free (DIN/VDE 0472, Part 815): 1
<b>Base colour:</b>	RAL 7035 -light grey			UV resistance: UL 508
<b>Cover screws material:</b>	Polyamide			Flammability Rating: UL 746C 5"
<b>Cover colour:</b>	Clear transparent			UL Type:
<b>Cover screws colour:</b>	Grey			Glow Wire Test (IEC 695-2-1) °C: 960
<b>Gasket material:</b>	Polyurethane			Certificates:
Temperatures:				Underwriters Laboratories
<b>Temperature °C (short term):</b>	-40 ... 120 °C			SGS Fimko
<b>Temperature °C (continuous):</b>	-40 ... 80 °C			UL Canada
<b>Temperature °F (short term):</b>	-40 ... 250 °F			Gost R
<b>Temperature °F (continuous):</b>	-40 ... 175 °F			

