

Catalog Number 01222

UPC Number 60198601222

Description Vinyl Insulated Male Disconnect 16-14



Features

- Vinyl Color Coded insulation for easy identification
- Manufactured from high strength copper alloy
- Electro-tin plated for corrosion resistance
- Easy entry expanded insulation eliminates strand "Hang Up", increases the crimping rates and the reliability of the wire
- Wire range stamped on the surface for easy interpretation
- Butted seams prevent splitting under maximum pressure
- Serrated barrel & flared position of sleeves provide excellent contact & mechanical stress relief at insulation & barrel junction
- Packed in Zip Lock plastic bags with punched hole for pegboard hanging


2.0		0.761
-	W	-
		1.

General

Insulation Type Vinyl Material Brass

Finish Electro-Tin Plated

Color Blue
Wire Range 16-14
Tab Size .020 X .187



Dimension Information

 Stock Thickness
 0.02

 L Inches (mm)
 0.748

 B Inches (mm)
 0.394

 C Inches (mm)
 0.091

 D Inches (mm)
 0.177

 F Inches (mm)
 0.256

 W Inches (mm)
 0.189

Specifications

Temperature Rating 167°F (75°C) Voltage Rating 300 V

Flammability Rating UL94V-O Amp Rating 15 Amps

Packaging

Bag Qty 25 Master Bag Qty 100

Certifications

UL Yes cUL Yes RoHS Yes

