

Catalog Number 01411


UPC Number 60198601411

Description Nylon Fully Insulated Female Disconnect 22-16



Features

- Nylon Color Coded insulation on barrel and disconnect tab
- Manufactured from high strength copper alloy
- Electro-tin plated for corrosion resistance
- Easy entry expanded insulation eliminates strand "Hang Up", increases the crimping rates and the reliability of the wire
- Wire range stamped on the surface for easy interpretation
- Brazed seams prevent splitting under maximum pressure
- Serrated barrel & flared position of sleeves provide excellent contact & mechanical stress relief at insulation & barrel junction
- Packed in Zip Lock plastic bags with punched hole for pegboard hanging



General

Insulation Type Nylon Material Brass

Finish Electro-Tin Plated

Color Red
Wire Range 22-16
Tab Size .032 X .250

Dimension Information

 Stock Thickness
 0.016

 L Inches (mm)
 0.866

 B Inches (mm)
 0.433

 C Inches (mm)
 0.067

 D Inches (mm)
 0.157

 F Inches (mm)
 0.287

 W Inches (mm)
 0.26

Specifications

Temperature Rating 167°F (75°C) Voltage Rating 300 V

Flammability Rating UL94V-O Amp Rating 10 Amps

Packaging

Bag Qty 25 Master Bag Qty 100

Certifications

UL Yes CUL Yes RoHS Yes

