



	<b>Specification Sheet for 12 awg 1 pair Power Limited Fire Alarm Cable, Plenum.</b>	<b>Rev Date:</b>	02/2014
		<b>SCP Part No.</b>	<b>12-2FPLP</b>
Approved: Andrew	Modified: Simon	<b>UL Type:</b>	<b>CL2P/FPLP</b>

DESCRIPTION: 2C/12 AWG SOLID FPLP PLENUM- RED- 1000 FT SPOOL

**Construction Details:**

This cable is constructed with one pair composed of 12 awg solid bare copper conductors insulated with a low smoke copolymer. The pair is cabled together and a jacket of red colored low smoke copolymer completes the package.

**Physical Specifications**

**Conductors:** 2 – 12 awg solid bare copper .081”

**Dielectric:** 10 mil wall of low smoke copolymer colored per the chart to a nominal diameter of .101”.

**Cabling:** Cable together two insulated conductors, per the color code, in a 3 1/2” left hand lay to a nominal diameter of .202”.

**Jacket:** 18 mil wall of red colored low smoke copolymer to a nominal diameter of .238”.

**Print:** Inkjet printing:  
  
12 AWG 2C PLENUM FIRE ALARM CABLE (UL)  
TYPE FPLP OR CL2P E198137

**Put Up:** Reels or boxes per customer requirements.

**Color Code**

Pair Number	Insulation Color
One	1-Black 1-Red