

SCP PART#: 14/2FPLP-XX

Rev04/22

Description :

2C/14 AWG SOLID FPLP PLENUM JKT - 1000 FT SPOOL

Part Number:	Jacket Color:
14/2FPLP	Red
14/2FPLP-BL	Blue
14/2FPLP-GR	Green
14/2FPLP-OR	Orange
14/2FPLP-YL	Yellow
14/2FPLP-WT	White

Conductor : 14 AWG Solid SBC Conductor

Total Cable Weight : 56 kg/km

Final Diameter : 0.206 inches

Insulation : PVC

Jacket : PVC

DC Resistance 25°C: 2.6 Ohms / 1000 ft

Mutual Capacitance : 24.6 pF/ft

Impedance : 73.7 Ohms

Velocity of Prop : 67 %

Inductance. : 1.2 mH/km

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 14/2FPLP - - - (UL) CL2P/CL3P
E198137 OR FPLP 75°C FT-6 UNSH 2/C 14 AWG SOLID --- ZONE/DEVICE A
B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Cabled OD Avg: 0.142

NEC Articles: 760 FPLP

Ins Thickness: 0.011

Min. Bend Radius/Minor Axis: 1.442 inches

Jkt Thickness: 0.017

Operating Temperature : -20°C to 75°C

Certified: UL CL2P/CL3P OR FPLP

Standard UL Temp : 60°C

Flame Rating: FT-6

Max Voltage: 300V

Package Weight: 37.50 lbs / 17.05 kgs

(All of the above values are approximated to within +/- 10%)