



Structured Cable Products™

Quality Installations Deserve Quality Products

www.scpcat5e.com
 sales@scpcat5e.com
 Direct: 954-327-5770
 Toll Free: 866-470-5742

SCP PART#: 14/2SH-GY

UPC: 810070018436

DESCRIPTION:

Shielded Riser 2/C 14/19 AWG SBC, PVC Insulation, Gray PVC Riser Jacket, 1000 FEET/305M

General Specification of Product :

Final Diameter :	0.227 inches	5.766 mm
Total Cable Weight:	62 kg/km	42 lbs/1000 ft
Conductor :	14 AWG 19 Stranded Bare Copper	
Insulation :	PVC	
Shield :	Foil Shield 0.075	
Drain \ Ground:	24 AWG 7 Stranded Tinned Copper	
Outer Jacket :	PVC	

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 14/2SH - - - (UL) CL3R
 E198137-SCP (UL) C(UL) CMR SHIELDED 2/C 14 AWG AUDIO ONLY - - -
 ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Electrical Characteristics :

DC Resistance 25°C:	2.6 Ohms / 1000 ft
Mutual Capacitance :	65 pF/ft
Cond to Shield Cap. :	119 pF/ft
Impedance :	35 Ohms
Velocity of Prop :	63 %

Cabled OD Avg: 0.158
 Ins Thickness: 0.011
 Jkt Thickness: 0.017
 Certified: UL CL3R / UL C(UL) CMR
 Flame Rating: Riser
 Max Voltage: 300V
 Packaging: Plywood Spool 12 x 7 x 5"
 Packaged Weight: 42 lbs / 20 kgs

(All of the above values are approximated to within +/- 10%)

QMS Registered ISO 9001

3091402.10S.1000