

SCP PART#: 16/4P

Description : 4C/16 AWG STRANDED BC - PLENUM - WHITE - 1000 FT SPOOL

02/22

General Specification of Product :

Final Diameter :	0.216 inches	5.486 mm
Total Cable Weight:	72.0 kg/km	48.4 lbs/1000 ft
Conductor :	4 Cond -16 AWG 26 Stranded Bare Copper	
Insulation :	PVC	
Outer Jacket :	PVC	

Print Notes : Sequentially marked per 2FT (0 - infinity)
Standard Print : STRUCTURED CABLE PRODUCTS --- P/N 16/4P --- (UL) CL2P/CL3P
 E198137-SCP OR FPLP 75°C (UL) C(UL) CMP FT-6 UNSH 4/C 16 AWG STR
 BC --- ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Electrical Characteristics :

DC Resistance 25°C:	4.1 Ohms / 1000 ft
Mutual Capacitance :	37.4 pF/ft
Impedance :	70 Ohms
Velocity of Prop :	62 %
Inductance. :	1.3 mH/km

Additional Information :

Cabled OD Avg: 0.186
Ins Thickness: 0.010
Jkt Thickness: 0.015
Certified: UL CL2P/CL3P OR FPLP / UL C(UL) CMP
Flame Rating: Plenum
Max Voltage: 300V
Packaging: Plywood Spool 12 x 12 x 5"
Packaging Weight: 50 lbs / 23 kgs

(All of the above values are approximated to within +/- 10%)