



Structured Cable Products®


Quality Installations Deserve Quality Products

www.scp5e.com
 sales@scp5e.com
 Direct: 954-327-5770
 Toll Free: 866-470-5742

SCP PART#: 16/4OFC-BK UPC: 810070019488

DESCRIPTION:

4C/16 AWG 65 STRAND OXYGEN FREE COPPER SPEAKER CABLE, UL CMR, PVC JKT- BLACK - 500 FT 152M BOX



Regulatory

- UL : UL 444 & UL 13, Type (UL) CMR/CL3 c(UL)
- EU RoHS 2011/65/EU Compliant
- EN50575: 2014 REACTION TO FIRE CLASS Dca

Application: Speaker cable

Construction Characteristics:

Conductor	Material	Stranded Bare Copper
	Size	16AWG X 4C(1.31mm ²)
	Construction	65/0.16mm +/-0.004mm
Insulation	Material	PVC
	Min.Thickness	0.30mm
	AVG.Thickness	0.33mm
	Diameter	2.0mm +/-0.10mm
	Colors	Black & Red & Green & White
Jacket	Material	PVC
	Min.Thickness	0.54mm
	AVG.Thickness	0.60mm
	Diameter	6.1mm +/-0.20mm
	Rip Cord	Nylon
	Color	Per request
Bend radius	Min 15D/95mm	



SCP PART#: 16/4OFC-BK	UPC: 810070019488
------------------------------	-------------------

DESCRIPTION:

4C/16 AWG 65 STRAND OXYGEN FREE COPPER SPEAKER CABLE, UL CMR, PVC JKT- BLACK - 500 FT 152M BOX

Electrical & Physical Characteristics:

Operating Temperature Range	- 20°C + 75°C		
Minimum installation temperature	0°C + 40°C		
Conductor Resistance	Max 15.5 ohm/km at 20°C		
Insulation Resistance	Min 50MΩ*km at 20°C		
Dielectric Strength	Min AC1.5KV		
Rated Voltage	300V		
Test Voltage	800V/min		
Impedance:			
opposite:	105 ± 8 Ω		
near by:	85 ± 8 Ω		
Capacitance:			
opposite:	18 ± 3pf/ft		
near by:	23 ± 3pf/ft		
Marking:	STRUCTURED CABLE PRODUCTS --- 16/4OFC --- E198137 SCP3 (UL) CL3 C(UL) CMR 4C 16AWG 65 STRAND OXYGEN FREE COPPER - EN50575:2014 CE Dca PVC JKT FT4 75C RoHS ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 ***FEET		
Packaging:			
Approx.Weight	Approx.Dimension(mm)	Package	Packages per pallet
11.8kgs/26.014lbs	320X260X320	500ft/ Box	36