

SCP PART#: 18/4P-500

Description : 4C/18 AWG STRANDED PLENUM - WHITE- 500 FT BOX

02/22

General Specification of Product :

Final Diameter : 0.184 inches 4.674 mm

Total Cable Weight: 46.0 kg/km 30.9 lbs/1000 ft

Conductor : 4 Cond -18 AWG 7 x.0152 Bare Copper

Insulation : PVC

Outer Jacket : PVC

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS --- P/N 18/4P --- (UL) CL2P/CL3P
E198137-SCP OR FPLP 75°C (UL) C(UL) CMP FT-6 UNSH 4/C 18 AWG STR
BC --- ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Electrical Characteristics :

DC Resistance 25°C: 6.7 Ohms / 1000 ft

Mutual Capacitance : 21.9 pF/ft

Impedance : 75 Ohms

Velocity of Prop : 61 %

Inductance. : 1.2 mH/km

Additional Information :

Cabled OD Avg: 0.138

Ins Thickness: 0.008

Jkt Thickness: 0.015

Certified: UL CL2P/CL3P OR FPLP / UL C(UL) CMP

Flame Rating: Plenum

Max Voltage: 300V

Packaging: Reelex Box 11.5 x 11.5 x 7.75"

Packaging Weight: 16 lbs / 7 kgs

(All of the above values are approximated to within +/- 10%)