




Structured Cable Products™

Quality Installations Deserve Quality Products

www.scpcat5e.com
 sales@scpcat5e.com
 Toll Free: 866-470-5742

SCP PART#: 18/4SHDB

DESCRIPTION: 4C/18AWG BC STRANDED SHIELDED
 DIRECT BURIAL,WBT,LLDPE JKT



Standard: NEC Article 760 & NEC Article 725

Construction Characteristics:

Conductor	Material	Stranded Bare Copper
	Size	18AWG X 4C
	Construction	16/0.254+/-0.004mm
Insulation	Material	PVC
	Min.Thickness	0.24mm
	AVG.Thickness	0.26mm
	Diameter	1.70+/-0.05mm
Shield	Colors	Black & Red & White & Green
	Core wrap	PE Tape
	Drain wire(TC)	7/0.20+/-0.004mm
	Shield	AL Foil
Jacket	Filler	Water proof
	Material	LLDPE
	AVG.Thickness	0.60mm
	Min.Thickness	0.54mm
	Diameter	6.20+/-0.20mm
	Rip Cord	Nylon
	Color	Black

Electrical & Physical Characteristics:

Operating Temperature Range		- 20°C + 70°C	
Conductor Resistance(18AWG)		Max 22.8ohm/km at 20°C	
Dielectric Strength		Min AC1.5KV	
Insulation PVC	Unaged	Tensile Strenght	13.8Mpa
		Elongation	100%
	Aged	Tensile Strenght	11.7Mpa(100°C 168h)
		Elongation	50%(100°C 168h)
Jacket	Unaged	Tensile Strenght	9.8Mpa
		Elongation	100%
	Aged	Tensile Strenght	9.2Mpa(100°C 168h)
		Elongation	50%(100°C 168h)

Marking:

STRUCTURED CABLE PRODUCTS --- 18/4SHDB ---4 COND 18 AWG STRANDED
 SHIELDED LLDPE JKT OUTDOOR/DIRECT BURIAL --- CE EU RoHS EC
 ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 ***FEET

Packaging:

Approx.Wight(kg)	Approx.Dimension(mm)	Package	Packages per pallet
18.50	360X180X160	1000ft/Spool	45