



SPECIFICATION SHEET

15-May-2014

Product Number : 22/2SOL-WT

RoHS

Description : 2C/22 AWG SOLID COPPER PVC- WHITE- 1000 FT BOX

Conductor : 22 AWG Solid HBC Cond.	
Total Cable Weight : 12 kg/km	Final Diameter : 0.105 inches
Insulation : PVC	Jacket : PVC
DC Resistance 25°C: 18.2 Ohms / 1000 ft	Mutual Capacitance : 21.2 pF/ft
Impedance : 87.1 Ohms	
Velocity of Prop : 66 %	Inductance. : 1.1 mH/km

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 22/2SOL - - - (UL) CL3R E198137
(UL) C(UL) CMR UNSH 1/PR 22 AWG - - - ZONE/DEVICE A B C D E 0 1 2 3 4
5 6 7 8 9 RoHS

Cabled OD Avg: Parallel	NEC Articles: 800, 725
Ins Thickness: 0.006	Min. Bend Radius/Minor Axis: .735 inches
Jkt Thickness: 0.015	Operating Temperature : -20°C to 60°C
Certified: UL CL3R/CMR	Standard UL Temp : 60°C
Flame Rating: Riser	
Max Voltage: 300V	

Package Weight: 8.5 lbs / 3.86 kgs

(All of the above values are approximated to within +/- 10%)