



222

20/2 Unshielded CMR

Audio and Control

Construction & Dimensions

| | |
|----------------------------|-----------------|
| CONSTRUCTION & DIMENSIONS | |
| CONDUCTOR PARAMETER | - |
| • Number of Conductors | 2 |
| • AWG Size | 20 |
| • Conductor Stranding | 7x28 |
| • Conductor Type | Bare copper |
| • Nominal DCR | 10.5 Ohm/1000ft |
| • Cabling Lay Length | 3 in |
| • Twists/Foot | 4 twist/ft |
| INSULATION PARAMETER | - |
| • Insulation Type | Th rmoplastic |
| • Insulation Thi kness | 0.007 in |
| • Insulation Color Code | 1. Black 2.Red |
| SHIELDING PARAMETER | - |
| • Shield Type | None |
| ELECTRICAL CHARACTERISTICS | - |

Overall Construction

| | |
|---------------------------------|----------|
| OVERALL CONSTRUCTION PARAMETERS | |
| Jacket Type | PVC |
| Jacket Thi kness | 0.017 in |
| Nominal Cable O.D. | 0.138 in |
| Plenum | No |
| NEC UL Rating | CMR, CMG |
| RoHS Compliant | Yes |
| Pull Tension | 26 lbs |
| Bend Radius | 1.242 in |
| Cable Weight | 15 lbs |

Overall Electrical & Optical Characteristics

| | |
|--|-----------------------|
| OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS | |
| UL Flammability | UL1666 Vertical Shaft |
| CSA Flammability | FT4 |
| Operating Range | -20 to 60 Deg C |
| UL Voltage Rating | 300 |

Related Products

| | |
|------------------|--------|
| RELATED PRODUCTS | |
| Plenum Number | 25222B |