



245

16/4 Unshielded CMR
 Audio, Control, and Low Voltage Power

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	
CONDUCTOR PARAMETER	
• Number of Conductors	4
• AWG Size	16
• Conductor Stranding	19x29
• Conductor Type	Bare copper
• Nominal DCR	4.2 Ohm/1000ft
• Cabling Lay Length	3.5 in
• Twists/Foot	3.4 twist/ft
INSULATION PARAMETER	
• Insulation Type	Th rmoplastic
• Insulation Thi kness	0.008 in
• Insulation Color Code	1.Black,2.Red,3.White,4.Green
SHIELDING PARAMETER	
• Shield Type	None
ELECTRICAL CHARACTERISTICS	

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	
Jacket Type	PVC
Jacket Thi kness	0.017 in
Nominal Cable O.D.	0.217 in
Plenum	No
NEC UL Rating	CMR, CMG
RoHS Compliant	Yes
Pull Tension	117 lbs
Bend Radius	1.953 in
Cable Weight	48 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	
UL Flammability	UL1666 Vertical Shaft
CSA Flammability	FT4
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

Detailed Specification & Technical Data



245

16/4 UTP CMR

Audio, Control, and Low Voltage Power

Related Products

RELATED PRODUCTS	
Plenum Number	25245B
Aquaseal Direct Burial Number	AQ245
4 Pole SpeakOn	CN-NL4FC
SpeakOn Panel Mount	CN-NL4MP