



Catalog Number 39030  
UPC Number 60198639030  
Description Button Style Photocell  
120 Volt




### Features

- Housing: UV stabilized impact resistant Polycarbonate  
Heavy-duty thermal bi-metal switch provides a 30+ second time delay  
Contact Position at Night is Normally Closed
- Sensor Type: CDS  
Single Pole, Single Throw Switch  
Power Consumption Below 1.5 Watts Average
- Load Switching Capability: 5,000 operations
- Load Rated: 1800W 1100VA  
3/4" Long 3/8" Threaded Nipple & Nut for 1/2" K.O.
- Operating Temperature: -23°C to +75°C

### General

Material: Polycarbonate Housing  
Switching: Single Pole, Single Throw  
Load Rating: 1800W 1100VA  
Sensor Type: Cadmium Sulfide CDS

Exterior dimension(mm)



### Dimension Information

Diameter: 2.15"  
Height: 1.7"  
Lead: 16AWG/18AWG, LENGTH 6"

### Specifications

Temperature Rating: -40°F – +150°F  
Voltage Rating: 120 V  
Frequency: 50-60 Hertz  
Turn-On Light Level: 10-16 Lux  
Turn-Off Light Level: <80 Lux  
Turn-On Time Delay: 30 sec  
Turn-Off Time Delay: 30 sec

### Packaging

Bag Qty 1  
Master Bag Qty 1

### Certifications

UL UL 773 Standard  
cUL  
RoHS

[www.morrisproducts.com](http://www.morrisproducts.com)

Morris Products 53 Carey Road, Queensbury, NY 12804