



## Industrial 4-Port Gigabit Ethernet PoE+ Switch with 2 SFP Ports

IEEE 802.3at/af (PoE+/PoE) Compliant, PoE Power Budget up to 120 W, IP40-Rated Metal Housing, Endspan, DIN-Rail Mount

Part No.: **508254**

EAN-13: 0766623508254 | UPC: 766623508254

### 4-Port Gigabit Ethernet PoE+ Industrial Switch with 2 SFP Ports — high-power PoE+ connectivity for harsh industrial environments

The 4-Port Gigabit Ethernet PoE+ Industrial Switch with 2 SFP Ports from Intellinet Network Solutions was designed to give you the network connections and device power you need in places that are less than calm or temperate. With a rugged, IP40-rated metal case it operates reliably and quietly, even in extreme temperatures that range from -40 to 167°F (-40 - 75°C). In combination with its DIN-rail mounting option and two safe redundant DC power inputs with power failure alarm and plenty of other safety features, this switch is ideal for IoT applications in Industry 4.0 and more.

### Gigabit Speeds paired with a large Power Budget

Featuring four auto-sensing 10/100/1000 Mbps RJ45 Gigabit Ethernet ports, this unmanaged switch offers plenty of performance for the devices in your network. The switch features a power budget of 120 W and can distribute a full 30 W (per the IEEE 802.3at standard) to every RJ45 port simultaneously. Also, two small form-factor pluggable GBIC module slots (SFP) provide fiber connectivity for greater distances.

#### Features:

For more information on Intellinet products, consult your local dealer or visit [www.intellinet-network.com](http://www.intellinet-network.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Provides power and data connections for up to four PoE network devices
- Save installation cost by delivering data and power over existing network cables
- IP40 slim-type metal housing to withstand harsh industrial conditions
- Wide operating temperature: -40 – 75°C (-40 – 167°F)
- Option for DIN-rail installation
- 10/100/1000 auto-sensing ports that automatically detect optimal network speeds
- Two small form-factor pluggable GBIC module slots (SFP)
- IEEE 802.3at/af-compliant RJ45 PoE/PoE+ output ports
- Power output up to 30 watts per port
- PoE power budget of 120 watts (depending on the power supply used)
- Two redundant DC inputs (44 – 57 V) with I/O terminal block
- Power failure alarm (one-way relay output, current load capacity 1 A @ 24 V DC)
- Port surge protection up to 6 kV
- Grounding point protects equipment from external electrical surges
- Rated for shock (IEC 60068-2-27), freefall (IEC 60068-2-32) and vibration (IEC 60068-2-6)
- 12 Gbps switch fabric
- Supports IEEE 802.3at and IEEE 802.3af-compliant PoE devices (wireless access points, VoIP phones, IP cameras, etc.)
- Supports IEEE 802.3at/af detection and short circuit, overload and high-voltage protection
- Auto-MDIX and NWay auto-negotiation support on all RJ45 ports
- Provides IEEE 802.1x port-based security
- Supports 4k MAC address entries with Auto-learning and Auto-aging
- Supports jumbo frames up to 9.6 kBytes
- Store and forward switching architecture
- Full/half duplex operation
- IEEE 802.3x flow control for full duplex
- LEDs for power, link/activity, PoE and SFP
- Fanless design for silent operation
- Requires additional industrial power supply (not included)
- Fully NDAA-compliant
- Three-year warranty

## Specifications:

### Standards

- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3ab (Twisted pair Gigabit Ethernet)
- IEEE 802.3af (Power over Ethernet 802.3at Type 1)
- IEEE 802.3at (Power over Ethernet 802.3at Type 2)
- IEEE 802.3i (Twisted pair 10BASE-T Fast Ethernet)
- IEEE 802.3u (100Base-TX Fast Ethernet)

For more information on Intellinet products, consult your local dealer or visit [www.intellinet-network.com](http://www.intellinet-network.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- IEEE 802.3x (Flow control for full-duplex mode)
- IEEE 802.3z (1000BASE-X Gigabit Ethernet)

#### General

- Media support:

RJ45 —

- 10Base-T: Cat3, 4, 5 UTP/STP

- 100Base-TX: Cat5 UTP/STP

- 1000Base-T: Cat5e UTP/STP

SFP —

- 1000Base-SX: 50  $\mu$ m / 62.5  $\mu$ m MMF (2 – 550 m)

- 1000Base-LX: 50  $\mu$ m / 62.5  $\mu$ m MMF (2 – 550 m) or 10  $\mu$ m SMF (2 – 5,000 m)

- Packet filter/forwarding rate:

- 893,000 pps (1,000 Mbps)

- 89,300 pps (100 Mbps)

- 8,930 pps (10 Mbps)

- MAC address table: 4k

• Backplane speed / switch fabric: 12 Gbps

• Switch architecture: store and forward

• Certifications: FCC Class A, CE, UKCA, NDAA

#### LEDs

- PoE
- Power
- Link/activity
- SFP

#### Pinout RJ45 output ports, mode A

- Pin 1: DC (+)
- Pin 2: DC (+)
- Pin 3: DC (-)
- Pin 6: DC (-)

#### Power

- DC input voltage: 44 – 57 V
- Power consumption: 135 watts (maximum)

#### Environmental

- Metal housing
- Dimensions: 162 (L) x 101 (W) x 35 (H) mm (6.38 [L] x 3.98 [W] x 1.38 [H] in.)
- Weight: 348 g (0.77 lbs.)
- Operating temperature: -40 – 75°C (-40 – 167°F)
- Operating humidity: 5 – 95% RH, non-condensing
- Storage temperature: -40 – 85°C (-40 – 185°F)

#### Package Contents

- 4-Port Gigabit Ethernet PoE+ Industrial Switch with 2 SFP Ports

- DIN-rail mount bracket

