



Gigabit High-Power PoE+ Injector

1 x 30 W Port, IEEE 802.3at/af Compliant, Plastic Housing

Part No.: **561518**

EAN-13: 0766623561518 | UPC: 766623561518

Provide both power and data to a Powered Device (PD) using existing Cat5 cable and this PoE Injector.

The Intellinet Network Solutions Gigabit High-Power PoE+ Injector lets you connect your IEEE 802.3af/at-compliant product to a non-PoE LAN switch port. The Power over Ethernet Injector can power and supply a network connection to a wireless access point, IP phone, network camera or any IEEE 802.3af/at-powered PD. This injector has an output power rating up to 30 watts. That's enough for even power-hungry PoE devices.

Reduce Wiring Costs.

There's no need to run AC power lines to get your PD set up and ready to do what it's supposed to. Simply connect the PoE Injector to the LAN switch port, and use the existing Cat5 cabling to deliver DC power as well as transfer data.

Protect Your Equipment.

Once DC power is connected to your networked equipment through the Cat5e/6 cabling, the Intellinet Network Solutions PoE Injector ensures that your products are protected from power problems like short circuits (short GND), current overloads and high voltages.

Features:

- Saves time and money by delivering data and power via existing

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

network cables

- IEEE 802.3at compliant (PoE+)
- Power output up to 30 watts
- Distance support: up to 100 m (328 ft.)
- Supports all IEEE 802.3at- and IEEE 802.3af-compliant PoE devices (Wireless LAN access points and bridges, VoIP [Voice over Internet Protocol] telephones, IP surveillance cameras and more)
- Supports IEEE 802.3at/af detection and short circuit, overload and high-voltage protection
- Internal power supply
- Fanless design ideal for silent operation
- Fully NDAA-compliant
- Three-year warranty

Specifications:

Standards

- IEEE 802.3af (Power over Ethernet)
- IEEE 802.3at (High-Power PoE+ Power over Ethernet)
- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3ab (Gigabit Ethernet)
- IEEE 802.3u (100Base-TX Fast Ethernet)
- IEEE 802.3x (flow control, for full duplex mode)

General

- Media support:
 - 100Base-TX Cat5 UTP/STP RJ45, 8 pin
 - 1000Base-T Cat5e UTP/STP RJ45, 8 pin
- Ports:
 - One RJ45 10/100/1000 Mbps input port
 - One RJ45 10/100/1000 Mbps data and power output port
- Protection functions:
 - Short circuit protection for short GND
 - Overload protection for currents over 0.6 A
- PoE Pinout: IEEE 802.3af/at Standard Mode A
 - Pin 1: DC (+)
 - Pin 2: DC (+)
 - Pin 3: DC (-)
 - Pin 6: DC (-)
- Certifications: FCC Class A, CE, RoHS, UKCA, NDAA

LED

- Dual-color power and PoE LED

Power

- Input: 100 – 240 V AC, 50 – 60 Hz
- Power consumption: 35 watts (maximum)

Environmental

- Plastic housing
- Dimensions: 136 (L) x 67 (W) x 34 (H) [mm] / 5.35 (L) x 2.64 (W) x 1.34 (H) [in.]
- Weight: 0.19 kg (0.42 lbs.)
- Operating temperature: 0 – 50°C (32 – 122°F)
- Operating humidity: 5 – 90% RH, non-condensing
- Storage temperature: -20 – 80°C (-4 – 176°F)

Package Contents

- Gigabit High-Power PoE+ Injector
- Power cable
- Instructions



For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

