

**60164B**

16/4 Unshielded Plenum Fire Alarm  
 Fire Alarm Signaling

**Construction & Dimensions**


CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	4
• AWG Size	16
• Conductor Stranding	Solid
• Conductor Type	Bare Copper
• Nominal DCR	4.1 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Plenum PVC
• Insulation Thi kness	0.008 in
• Insulation Color Code	1.Black,2.Red,3.Brown 4.Blue
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	33 pF/ft

**Overall Construction**

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	Flexible Plenum
Jacket Thi kness	0.015 in
Nominal Cable O.D.	0.191 in
Plenum	Yes
NEC UL Rating	FPLP
RoHS Compliant	Yes
Pull Tension	108 lbs
Bend Radius	1.719 in
Cable Weight	44 lbs

**Overall Electrical & Optical Characteristics**

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	NFPA 262 Plenum
Operating Range	-0 to 60 Deg C
UL Voltage Rating	300



**60164B**

16/4 Unshielded Plenum Fire Alarm  
Fire Alarm Signaling

**Related Products**

RELATED PRODUCTS	-
Non Plenum Number	992
Aquaseal Direct Burial Number	AQ245