

Catalog Number UPC Number Description

Features

• Completely Self-Contained • Fully Automatic Operation

• 120 or 277 VAC Operation

Listed for Damp Location

• Compact, Low Profile Design in Neutral Finish • Push to Test Switch in Battery Backup Units • Automatic, Low Voltage Disconnect (LVD)

• Charge Rate/Power On LED Indicator Light


73010 sing ackup

Superior Quality Exit Unit Combined with LED Energy Saving Technology

• Injection-Molded, UL 94 V-0 Flame Retardant, High Impact Housing

• Energy Consumption Less than 4 W Red Legend 2 W Green legend





60198673010
Exit Sign
LED
Red Letters White House
AC Only - No Battery Ba

 Universal Mounting Canopy & 2 Face Plates for Side or Top Installation **Dimension Information** 12.00 L Inches H Inches 7.50 Depth Inches (mm) 1.50 Specifications 18.1 mA @120V, 7.76 mA @ 277V Input Rating Amps: Input Rating Watts: 1.64W @ 120V 1.60W @ 277V Frequency: 60 Hz 120/277 Voltage Rating: Flammability Rating: UL94V-0 Packaging

## Box Qty Ma

laster Carton	Qty	6

Certifications	
UL	UL 924
cUL	No
RoHS	Yes

1

Morris Products 53 Carey Road, Queensbury, NY 12804 www.morrisproducts.com