

Catalog Number UPC Number Description

73013 60198673013 Exit Sign LED

Red Letters Black Housing




- Superior Quality Exit Unit Combined with LED Energy Saving Technology Completely Self-Contained
- Fully Automatic Operation
- Compact, Low Profile Design in Neutral Finish
- Push to Test Switch in Battery Backup Units
- Automatic, Low Voltage Disconnect (LVD)
- 120 or 277 VAC Operation
- Injection-Molded, UL 94 V-0 Flame Retardant, High Impact Housing
- Charge Rate/Power On LED Indicator Light
- Energy Consumption Less than 4 W Red Legend 2 W Green legend
- Listed for Damp Location
- Universal Mounting Canopy & 2 Face Plates for Side or Top Installation
- Standard AC and Emergency Units Available

12.00

7.50

- 700MAH 4.8V Ni-CAD Battery On Battery Backup Units
- 90 Minute Battery Run Time

Dimension Information



Depth Inches (mm)	1.50
pecifications	
nput Rating Amps:	18.1 mA @120V, 7.76 mA @ 277V
nput Rating Watts:	1.64W @ 120V 1.60W @ 277V
requency:	60 Hz
oltage Rating:	120/277
lammability Rating:	UL94V-0
Battery Operation:	4.8 Volt 4.5 AH Lead Acid - 90 Minutes Min

Packaging

L Inches

Certifications	
UL	UL 924
cUL	No
RoHS	Yes