



Catalog Number 73054
 UPC Number 60198673054
 Description Combination Exit/Emergency Light
 LED Sign
 LED Lamps

Features

- Completely Self-Contained
- Fully Automatic Operation
- Compact, Low Profile Designs in Neutral Finish
- Push to Test Switch
- 6-Volt Maintenance Free Ni-Cad Battery
- Environmental Coated, Solid State Charger
- 2 x 12 LED Fully Adjustable Glare Free Lamps
- Automatic, Low Voltage Disconnect (LVD)
- Universal Transformer for 120 or 277 VAC
- Universal J-Box Mounting Plate
- Injection Molded, V-O Flame Retardant, High Impact, Thermoplastic Housing
- Integral wiring channels for ease of installation
- Charge Rate/Power on LED Indicator Light
- 90 Minute Emergency Operation
- Rated for Damp Location



Dimension Information

L Inches (mm) 11.60
 H Inches (mm) 7.20
 Depth Inches (mm) 2.00

Specifications

Input Rating Amps: 31.1 mA @ 120V, 12.9 mA @277V
 Input Rating Watts: 4.12W @ 120V, 3.2W @ 277V
 Output Load: 10.8W Integral
 Lamp Type: LED - 12 LED Per Head 76 Lumens Per Head
 Lamp Lumen Output: 76 Lumens Per Head
 Voltage Rating: 120/277
 Frequency: 60 Hz
 Flammability Rating: UL94V-0
 Battery Operation: 6 Volt Nickel Cadmium - 90 Minutes Minimum

Packaging

Box Qty 1
 Master Carton Qty 6

Certifications

UL UL 924
 cUL No
 RoHS Yes

Cat No.	Width	Depth	Height	Led Color	Housing	Lumens Per Head	Case Qty
73054	11.60"	2.00"	7.20"	Red	White	76	6
73055	11.60"	2.00"	7.20"	Red	Black	76	6
73056	11.60"	2.00"	7.20"	Green	White	76	6
73057	11.60"	2.00"	7.20"	Green	Black	76	6