



Features

· Completely Self-Contained

· Fully Automatic Operation

· Compact, Low Profile Designs in Neutral Finish

· Push to Test Switch

· 3.6 Volt Maintenance Free Ni-Cad Battery

· Environmental Coated, Solid State Charger

· 2 x 12 LED 132 Lumen Fully Adjustable Glare Free Lamps

· Automatic, Low Voltage Disconnect (LVD)

· Universal Transformer for 120 or 277 VAC


· Universal J-Box Mounting Plate

· Injection Molded, V-O Flame Retardant, High Impact, Thermoplastic Housing

· Charge Rate/Power on LED Indicator Light

· 90 Minute Emergency Operation

· Damp Location Rated



Dimension Information

L Inches (mm) 9 H Inches (mm) 4.00 Depth Inches (mm) 2.75

Specifications

Input Rating Amps: .103A@120V .105A@277V Input Rating Watts: .85W@120V .8W@277V

Output Rating Watts: 3.44W

Lamp Type: LED 132 Lumens Per Head

Voltage Rating: 120/277 Flammability Rating: UL94V-0

Battery Operation: 3.6 Volt Nickel Cadmium - 90 Minutes Minimum

Packaging

Box Qty 1 Master Carton Qty 12

Certifications

UL UL 924 cUL No ROHS Yes

Warranty

Five Years