



Catalog Number UPC Number Description 73118 60198673118 LED Emergency Light LED Lamps

Features

- Completely Self-Contained
- Fully Automatic Operation
- Compact, Low Profile Designs in Neutral Finish
- Push to Test Switch
- 2.4 Volt Maintenance Free Ni-Cad Battery
- Environmental Coated, Solid State Charger
- 2 x 12 LED 76 Lumen Fully Adjustable Glare Free Lamps
- Automatic, Low Voltage Disconnect (LVD)
- Universal Transformer for 120 or 277 VAC
- Universal J-Box Mounting Plate
- Injection Molded, V-O Flame Retardant, High Impact, Thermoplastic Housing
- Charge Rate/Power on LED Indicator Light
- 90 Minute Emergency Operation
- Damp Location Rated

| Dimension Information | |
|-----------------------|------|
| L Inches (mm) | 9 |
| H Inches (mm) | 4.00 |
| Depth Inches (mm) | 2.75 |
| | |

Specifications

| Input Rating Amps: | 0.06 |
|----------------------|--|
| Input Rating Watts: | 6.7 @ 120V 7.3 @ 277V |
| Output Load: | 10.8W Integral |
| Lamp Type: | LED 76 Lumens Per Head |
| Voltage Rating: | 120/277 |
| Flammability Rating: | UL94V-0 |
| Battery Operation: | 2.4 Volt Nickel Cadmium - 90 Minutes Minimum |
| | |

Packaging

Box Qty Master Carton Qty

| Certifications | |
|----------------|--------|
| UL | UL 924 |
| cUL | No |
| RoHS | Yes |

1

12

