




Catalog Number See Table
UPC Number
Description Four Conductor Vertical Stacked Aluminum Mechanical Lug Two Mounting Holes

- Features**
- Manufactured from High Strength High Conductivity Aluminum Alloy
 - Electro-Tin Plated
 - CU-AL Dual rated for AL/AL, AL/CU, CU/CU Applications
 - Four Conductor Two Hole Configuration - Stacked

General

Material: 6061-T6 Aluminum Alloy
 Finish: Electro-Tin Plating
 Screw Type: Hex Head
 Wire Range: 3/0 - 750 MCM

Dimension Information See Table



Specifications

Temperature Rating 90° C
 Voltage Rating 600
 Flammability Rating N/A
 Amp Rating To Conductor

Packaging

Box Qty See Table

Certifications

UL UL 486B UL41968 CU9AL Dual Rated
 CSA
 RoHS Yes

| Cat. | | Wire | Box | | | | Hole | | |
|---------------------------------------|-----|------------------|-----|------|------|---|-------|------|--|
| No. | AWG | Range | Qty | L | W | H | Space | Bolt | |
| PANELBOARD LUGS - 4 CONDUCTORS | | | | | | | | | |
| 90924 | 600 | 600MCM - 3/0STR. | 1 | 4.94 | 2.5 | 3 | 1.38 | 0.41 | |
| 90926 | 750 | 750MCM - 3/0STR. | 1 | 4.94 | 2.63 | 3 | 1.38 | 0.41 | |