



Catalog Number See Table
UPC Number
Description One Conductor Two Hole Mount
 Aluminum Mechanical Lug

Features

- Manufactured from High Strength High Conductivity Aluminum Alloy
- Electro-Tin Plated
- CU-AL Dual rated for AL/AL, AL/CU, CU/CU Applications
- One Conductor Two Mounting Hole Configuration
2 Set Screws

General
 Conductor Size: See Table
 Material: 6061-T6 Aluminum Alloy
 Finish: Electro-Tin Plating
 Screw Type: 2 - Hex Head Screws
 Wire Range: 600 Thru 1000 MCM

Dimension Information
 See Table

Specifications
 Temperature Rating 90° C
 Voltage Rating 600
 Flammability Rating N/A
 Amp Rating To Conductor

Packaging
 Box Qty See Table

Certifications
 UL UL 486B UL41968 CU9AL Dual Rated
 CSA LR 27194
 RoHS Yes

Cat No.	AWG	Fig.	Wire Range	Box Qty	L	W	H	Bolt	
ONE CONDUCTOR - TWO HOLE MOUNT									
90941	600	9	600MCM - 4SOL	3	5.19	1.25	1.56	0.56	
90942	750	9	800MCM - 300MCM	3	4.72	1.44	1.81	0.56	
90944	1000	9	1000MCM - 500MCM	3	4.81	1.62	1.94	0.56	