



Catalog Number Various
UPC Number Various
Description Aluminum Long Barrel 2 Hole Compression Connector




Features

- Manufactured from High Strength High Conductivity Seamless Aluminum
- Electro-Tin Plated
- AL9CU Dual Rated for Copper or Aluminum Conductors
- Oxide Inhibitor filled/capped barrel
- Color coded & Marked with die size and crimp marks

General

Wire Size 1/0 thru 750 MCM
Material High Conductivity Seamless Aluminum
Material Treatment Electro-Tin Plating
Stud Configuration 2 Hole NEMA Spacing



Dimension Information

See Table

Specifications

Temperature Rating 90° C
Voltage Rating 35 KV
Flammability Rating N/A
Amp Rating To Conductor

Packaging

Box Qty see table

Certifications

UL UL486B AL9CU
cUL Yes
RoHS Yes

Cat No.	Wire Range	Stud Size	Color Code	Box Qty	Inside Diameter	Outside Diameter	A	A1	B	C	D	E	F	G
93110	1/0 Str.	3/8	Tan	10	.39(9.91)	.63(16.00)	3.50(88.9)	1.2(30.5)	.85(21.5)	.24(6.1)	.41(10.4)	.38(9.6)	1.87(47.5)	1.00(25.4)
93111	1/0 Str.	1/2	Tan	20	.39(9.91)	.63(16.00)	4.75(120.6)	1.2(30.5)	.85(21.5)	.24(6.1)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)
93112	2/0 Str.	1/2	Olive	20	.44(11.18)	.69(17.53)	4.80(121.9)	1.3(33.0)	.94(23.8)	.24(6.1)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)
93114	3/0 Str.	1/2	Ruby	20	.48(12.19)	.76(19.30)	5.00(127.0)	1.4(35.6)	1.03(26.1)	.28(7.1)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)
93116	4/0 Str.	1/2	White	12	.55(13.97)	.84(21.34)	5.25(133.3)	1.4(35.6)	1.15(29.2)	.29(7.3)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)
93118	250 MCM	1/2	Red	12	.59(14.99)	.92(23.37)	5.31(134.8)	1.5(38.1)	1.26(32.0)	.32(8.1)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)
93120	300 MCM	1/2	Blue	9	.65(16.51)	1.01(25.65)	5.50(139.7)	1.6(40.6)	1.37(34.8)	.35(8.8)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)
93122	350 MCM	1/2	Brown	6	.72(18.29)	1.12(28.45)	5.87(149.1)	1.9(48.3)	1.52(38.6)	.39(9.9)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)
93124	400 MCM	1/2	Green	6	.76(19.30)	1.19(30.23)	6.43(163.3)	2.3(58.4)	1.61(40.8)	.42(10.6)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)
93126	500 MCM	1/2	Pink	6	.84(21.34)	1.32(33.53)	6.50(165.1)	2.5(63.5)	1.79(45.4)	.47(11.9)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)
93128	600 MCM	1/2	Black	4	.92(23.37)	1.44(36.58)	6.75(171.4)	2.6(66.0)	1.96(49.7)	.51(12.9)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)
93130	750 MCM	1/2	Yellow	4	1.03(26.16)	1.60(40.64)	7.37(187.2)	3.2(81.3)	2.19(55.6)	.55(13.9)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)