



Catalog Number See Table
UPC Number
Description Copper Long Barrel Compression Splice




Features

- Manufactured from High Strength High Conductivity Seamless Copper Tubing
- Electro-Tin Plated
- Color coded & Marked with die size and crimp marks

General

Wire Size #8 Str thru 1000 MCM
Material High Conductivity Seamless Copper Tubing
Material Treatment Electro-Tin Plating



Dimension Information

See Table

Specifications

Temperature Rating 90° C
Voltage Rating 35 KV
Flammability Rating N/A
Amp Rating To Conductor

Packaging

Box Qty See Table

Certifications

UL UL486A
cUL Yes
RoHS Yes



Copper Long Barrel Compression Splice

Cat No.	Wire Range	Color Code	Box Qty	Inside Diameter	Outside Diameter	Length	Each
94510	8 Str.	Red	60	.172(4.4)	.272(6.9)	2.01(51.1)	
94512	6 Str.	Blue	40	.203(5.2)	.297(7.5)	2.36(59.9)	
94514	4 Str.	Gray	25	.250(6.4)	.344(8.7)	2.36(59.9)	
94516	2 Str.	Brown	18	.315(8.0)	.422(10.7)	2.60(66.0)	
94518	1 Str.	Green	15	.360(9.1)	.469(11.9)	2.87(72.9)	
94520	1/0 Str.	Pink	10	.390(9.9)	.520(13.2)	2.87(72.9)	
94522	2/0 Str.	Black	20	.441(11.2)	.563(14.3)	3.11(79.0)	
94524	3/0 Str.	Orange	16	.492(12.5)	.622(15.8)	3.11(79.0)	
94526	4/0 Str.	Purple	12	.547(13.9)	.688(17.5)	3.39(86.1)	
94528	250 MCM	Yellow	12	.594(15.1)	.750(19.1)	3.39(86.1)	
94530	300 MCM	White	9	.658(16.7)	.813(20.7)	4.13(104.9)	
94532	350 MCM	Red	6	.700(17.8)	.875(22.2)	4.13(104.9)	
94534	400 MCM	Blue	6	.764(19.4)	.949(24.1)	4.37(111.0)	
94536	500 MCM	Brown	6	.835(21.2)	1.063(27.0)	4.61(117.1)	
94538	600 MCM	Green	4	.925(23.5)	1.188(30.2)	5.35(135.9)	
94540	750 MCM	Black	4	1.03(26.2)	1.31(33.3)	5.87(149.1)	
94542	1000 MCM	—	1	1.19(30.2)	1.53(38.8)	6.12 (155.4)	