

AQ3245

16/4 Shielded Indoor/Outdoor Direct Burial CL3/FPL Rated
Audio and Control

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	4
• AWG Size	16
• Conductor Stranding	19x29
• Conductor Type	Bare copper
• Nominal DCR	4.2 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	PVC
• Insulation Thickness	0.02 in
• Insulation Color Code	1.Black,2.Red,3.Blue ,4.Brown
SHIELDING PARAMETER	-
• Shield Type	Aquaseal Water Blocking Tape
• Shield Type 2	Aquaseal Water Blocking Tape
• Drain Wire Type	Tinned Copper
• Drain Wire AWG	24 AWG
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	27 pF/ft
• Nom. Cap. Conductor to Shield	67 pF/ft


Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	UV Resistant PVC
Jacket Thickness	0.04 in
Nominal Cable O.D.	0.415 in
Plenum	No
NEC UL Rating	CL3, FPL, PLTC
RoHS Compliant	Yes
TIA Test	TIA455-82 Water Penetration Test
Bend Radius	3.735 in
Cable Weight	89 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-20 to 90 Deg C

Detailed Specification & Technical Data



AQ3245

16/4 Shielded Indoor/Outdoor Direct Burial CL3/FPL Rated
Audio and Control

Related Products

RELATED PRODUCTS	-
Non Plenum Number	3245