



AQC226

2 Conductor 14 AWG Unshielded Indoor/Outdoor
Audio, Control, Alarm Indoor/Outdoor



Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	2
• AWG Size	14
• Conductor Stranding	19x27
• Conductor Type	Bare Copper
• Nominal DCR	2.7 Ohm/1000 ft
INSULATION PARAMETER	-
• Insulation Type	PVC
• Insulation Thickness	0.015 in
• Insulation Color Code	1. Black, 2. Red
SHIELDING PARAMETER	-
• Shield Type	Aquaseal Water Blocking Tape
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	34 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	UV Resistant PVC
Jacket Thickness	0.025 in
Nominal Cable O.D.	0.294 in
Plenum	No
NEC UL Rating	CL3, FPL
RoHS Compliant	Yes
TIA Test	TIA455-82 Water Penetration Test
Pull Tension	82 lbs
Bend Radius	2.646 in
Cable Weight	48 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-20 to 90 Deg C
UL Voltage Rating	300



AQC226

2 Conductor 14 AWG Unshielded Indoor/Outdoor
Audio, Control, Alarm Indoor/Outdoor

Related Products

RELATED PRODUCTS	-
Plenum Number	25226B
Non Plenum Number	226
Aquaseal Direct Burial Number	AQ226
4 Pole SpeakOn	CN-NL4FC
SpeakOn Panel Mount	CN-NL4MP