



AQC359

4 Conductor (2 Shielded, 2 Unshielded) Indoor/Outdoor CM
 Rated Audio, Control, Alarm Indoor/Outdoor



Construction & Dimensions

CONSTRUCTION & DIMENSIONS		-
Component	Shielded	Unshielded
CONDUCTOR PARAMETER		-
• Number of Conductors	2	2
• AWG Size	20	20
• Conductor Stranding	7x28	7x28
• Conductor Type	Bare Copper	Bare Copper
• Nominal DCR	10.1 Ohm/1000 ft	10.1 Ohm/1000 ft
INSULATION PARAMETER		-
• Insulation Type	PVC	PVC
• Insulation Thickness	0.01 in	0.01 in
• Insulation Color Code	1. Black, 2. Red	1. White, 2. Green
SHIELDING PARAMETER		-
• Shield Type	Overall 100% Aluminum Foil	None
• Shield Type 2	Aquaseal Water Blocking Tape	
• Drain Wire Type	Tinned Copper	
• Drain Wire AWG	22 AWG	
ELECTRICAL CHARACTERISTICS		-
• Nom. Cap. Between Conductors	60 pF/ft	
• Nom. Cap. Conductor to Shield	108 pF/ft	

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Total Number of Conductors	4
Jacket Type	UV Resistant PVC
Jacket Thickness	0.025 in
Nominal Cable O.D.	0.266 in
Plenum	No
NEC UL Rating	CM, CL3
RoHS Compliant	Yes
TIA Test	TIA455-82 Water Penetration Test
Pull Tension	65 lbs
Bend Radius	2.394 in
Cable Weight	28 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-20 to 90 Deg C
UL Voltage Rating	300

Detailed Specification & Technical Data



AQC359

4 Conductor (2 Shielded, 2 Unshielded) Indoor/Outdoor CM
Rated Audio, Control, Alarm Indoor/Outdoor



Related Products

RELATED PRODUCTS	-
Plenum Number	25359B
Non Plenum Number	359