

BG-ADAMO-4KND

4K@60Hz 12G-SDI/HDMI 2.0/USB 2.0/ USB 3.0/NDI\HX Live Streaming PTZ Camera with Tally Lights (Available in black & white)

BZBGEAR is proud to announce the next generation of PTZ cameras: the BG-ADAMO-4KND. Brilliantly designed with a unique form factor, the BG-ADAMO-4KND is unrivaled in the live stream broadcasting market.

The 12G-SDI connection enables long distance cable runs without compromising image quality. Capable of storing 1 TB of video footage with the microSDXC card writer, start recording on the fly when other connections are inaccessible. With NDI|HX® support and LED tally lights that illuminate either green or red with 360-degree visibility, the Adamo is a game changer!



Pristine Detail, Accurate Color, Quiet Operation

- Optical zoom lens: 12x (25 ft), 25x (50 ft)
- 4K@60Hz resolutions provide fluid motion, clear image, and accurate colors
- Auto focusing algorithms resulting in quick, accurate, and stable focus

Digital and Analog Control at Your Fingertips

- Web interface control via the IP address; camera preview access
- IR remote control
- Supports IP and serial control protocols (Visca IP, ONVIF / Pelco-P/D, Visca)
- Free BG-PTZ-Control app/program for Apple devices, PCs, NDI Tools

Unrivaled Diversity of Connections and Streaming Formats

- Supports RTSP, RTMP, RTMPS, ONVIF, and GB/T28181
- + 12G-SDI, HDMI, USB 2.0/3.0, LAN NDI|HX / Power over Ethernet
- H.264/H.265 video compression formats provide excellent image quality
- 3.5 mm input for embedding audio into your live stream

Compatible Live Streaming Software & Online Platforms

- vMix, Wirecast, Echo360, Zoom, Skype, Meet, GoToMeeting, & more
- YouTube, Facebook, Linkedin, Instagram, Twitter, Twitch, & more





FREE Software Control Program BG-PTZ-CONTROL

Specifications

BG-ADAMO-4KND		
HDMI Video Output	3840*2160p@60Hz/50/30/25/59.94/29.97 - 1080p@60Hz/50/30/25/59.94/29.97 1080i@60Hz/50/30/59.94 - 720p@60Hz/50/59.94	
12G-SDI Video Output	3840*2160p@60Hz/50/30/25 - 1080p@60Hz/50/30/25 - 720p@60Hz/50	
USB 3.0 Video Output	YUY2: 1920*1080/1600*896 /1280*720 /1024*576 /960*540 /800*600/800*448 /720*576/720*480/P60/50/30/2 NV12: 1920*1080/1600*896 /1280*720 /1024*576 /960*540 /800*600/800*448 /720*576/720*480/P60/50/30/2	
USB 2.0 Video Output	MJPG: 3840*2160p@30Hz; 1920*1080/1600*896 /1280*720 /1024*576 /960*540 /800*600/800*448 /720*576/720*480/640*480 /640*360 /480*270 /352*288/320*240P60/50/30/25; H264 : 3840*2160P30; 1920*1080 /1600*896 /1280*720 /1024*576 /960*540 /800*600 /800*448/720*576/720*480/640*480 /640*360 /480*270/352*288/320*240P60/50/30/25; YUY2 : 640*360 /480*270 /320*180p@30Hz/25 NV12 : 640*480 /640*360 /480*270 /320*180p30Hz/25	
LAN Video Output Format	Main stream:3840*2160/5-30fps; 1920*1080/5-60fps; 1280*720/5-60fps Substream:720*480; 640*480; 640*360; 320*240; 320*180/5-30fps	
Dimensions (LxWxH)	248 x 191 x 210 mm	

AT A GLANCE	SUITABLE APPLICAT
Zoom	Business Conference Roo
12x, 25x Optical Zoom	Healthcare
Video Output(s)	Education
12G-SDI, HDMI, USB 2.0, USB 3.0, NDI HX - LAN	Houses of Worship
Audio Input(s)	Live Events
3.5 mm	
Control	
RS232, RS485, LAN, IR Remote	
Power Connections	
Power Supply, Power over Ethernet	

Industry-Leading Warranty & Support

BZBGEAR Pro AV products and Cameras come with a three-year warranty. An extended two-year warranty is available for our Cameras upon registration for a total of five years.

We pride ourselves in our Customer Service and seven-days-a-week Tech Support.



ATIONS

Rooms



830 National Drive, Suite 140 Sacramento, CA 95834 1.888.499.9906 info@bzbgear.com