


DESCRIPTION

Category 6 V-Max Keystone Jack Unshielded - TAA-Compliant Lifetime Warranty

FEATURES

- Color Coded for T568A and T568B standards
- Meets and Exceeds ANSI/TIA-568.2-D, ANSI/TIA 1096-A
- Supports PoE 802.3af, 802.3at, 802.3bt
- Fits most standard keystone wall plates and patch panels
- Narrow connector allows high port density in small areas
- Compatible with standard 110 punch down tool
- Use the V-Max I-Punch Tool for faster termination
- Available in various colors for easy Identification
- UL Listed, RoHS Compliant, TAA Compliant
- 25 pack (single package)



VERTICAL CABLE

800.749.2447 Florida 951.696.7772 California 845.391.8318 New York

CAT6 UNSHIELDED KEYSTONE JACK (V-MAX Series)

SKU: 352 SERIES

Height	Width	Depth	Weight (single jack)	Weight (25 Pack)
0.78 in	0.67 in	1.22 in	0.04 lb	0.5 lb


Specifications				
RJ45 Jack				
Housing Material	ABS+PC UL 94V-0			
Contact Bracket	PBT+Glass Fiber, UL 94V-0			
RJ45 Jack Contact				
Material	Phospor Bronze with Nickel plating			
Finish	50 micro-inch Gold plating on Plug contact area			
IDC				
Housing	PC UL 94V-0 with Black color			
Terminal	Phospor Bronze with Tin plated			
Сар	ABS+PC UL 94V-0			
PCB	FR4, UL 94V-0			
Performance				
Color Code	T568A & T568B wiring			
Insertion Force	20N max. (IEC 606037-4)			
Retention Strenght	17LB (7.7kg) between jack and plug			
Operating Temp	-10°C to 60°C max (ISO/IEC 11801, ANSI/TIA 568 C.2)			
Operating Life (mating cycles)				
Jack	Minimum 750 cycles min. (ISO/IEC 11801, IEC 60603-7-4)			
IDC	Suitable for 23 and 24AWG solid wire			
Colors available				
Black, Blue, Gray, Green, Iv	vory, Yellow, Red, White, Orange, Purple			



































VERTICAL CABLE

800.749.2447 Florida 951.696.7772 California 845.391.8318 New York