

T502-Ch Amplifier





This 2-channel class D power amplifier features a mono or stereo speaker output, with support for 4-ohm and 8-ohm speakers. It can deliver 50 watts per channel into 8-ohm loads or 60 watts per channel into 4-ohm loads. Stereo looping outputs allow you to chain amplifiers together to create additional audio zones. Budget-friendly and versatile, it is compatible with dual voltage 110V/220V, can be programmed to work with any TV or control system and you can easily add bass with the sub-out. IR remote and wall-mount brackets are included. Optional AMP-CAN allows amp to easily disappear behind the TV.





T50 2-Ch Amplifier





Channels: **Power Output, Continuous:**

Bridged Power Output:

Power Requirements: Impedance: Inputs:

Outputs: Control:

Dimensions:

Weight: Certifications:

Family:

T50

2 Channels 2 Channels
50 Watts / Ch @ 8Ω
60 Watts / Ch @ 4Ω
100 Watts / Ch @ 8Ω
60 Watts / Ch @ 4Ω
120V - 240V @ 50 Hz - 60 Hz A/C
4 - 8 Ω
(1) Storce PCA (1) T-C

(1) Stereo RCA, (1) ToS (1) 3.5mm, (1) Subwoofer (with option of

70Hz crossover or full range)
(1) 3.5mm IR with built in learning. IR receiver also included

1.75" (44.5mm) H 6.5" (165mm) W 5.2" (132mm) D 2.25 lbs

CE, FCC

UNIVERSAL



Optional AMP-CAN Easily install the T50 discreetly behind a TV or other equipment.

