

# Thin Wall Heat Shrink Tubing - Kits



68320



68321

Dimensions = Inches

Cat. No.	Kit Type	Contents				
		Length	Color	Diameter Before Shrinking	Diameter After Shrinking	Total Pieces
<b>Colored Kit</b>						
68320	Colored Kit	1.375	(5)Red, (5)Blue, (5)White, (5)Yellow	.078	.029	20
		1.375	(5)Red, (5)Blue, (5)White, (5)Yellow	.098	.039	20
		1.375	(5)Red, (5)Blue, (5)White, (5)Yellow	.137	.059	20
		1.375	(5)Red, (5)Blue, (5)White, (5)Yellow	.212	.098	20
		2.953	(3)Red, (2)Blue, (3)White, (2)Yellow	.251	.117	10
		2.953	(1)Red, (2)Blue, (1)White, (1)Yellow	.370	.176	5
		2.953	(1)Red, (2)Blue, (1)White, (1)Yellow	.488	.236	5
<b>Black Kit</b>						
68321	Black Kit	1.375	(20)Black	.078	.029	20
		1.375	(20)Black	.098	.039	20
		1.375	(20)Black	.137	.059	20
		1.375	(20)Black	.212	.098	20
		2.953	(10)Black	.251	.117	10
		2.953	(5)Black	.370	.176	5
		2.953	(5)Black	.488	.236	5

Heat Shrink

E4

# Medium Wall Heat Shrink Tubing - 3:1 Shrink Ratio



Dimensions = Inches

- ▶ 3:1 Shrink Ratio
- ▶ Suitable for Electrical and Mechanical Applications where Lighter Weight and Flexibility are Important
- ▶ Seals and Protects Cable Splices and Terminations
- ▶ High Resistance to Impact and Abrasion
- ▶ 4' Lengths have Adhesive Liner for Complete Environmental Protection and Insulation
- ▶ Continuous Operating Temperature:
  - ▶ -67°F to 230°F (-55°C to 110°C)
  - ▶ Shrink Temperature: 248°F (120°C)
- ▶ Rated for 600-2500V
- ▶ UL486D
- ▶ Black Color

Cat. No.	Cable Range	Length	Diameter Before Shrinking	Diameter After Shrinking	Wall Thickness
68112	12-6	4 FT	.40	.15	.080
68114	8-1/0	4 FT	.75	.22	.080
68116	2-4/0	4 FT	1.10	.40	.080
68118	--	4 FT	1.30	.40	.080
68120	3/0-400	4 FT	1.50	.50	.080
68122	-	4 FT	1.70	.50	.080
68124	250-750	4 FT	2.05	.75	.080
68126	-	4 FT	2.75	1.00	.080
68128	800-1250	4 FT	3.50	1.18	.095
68130	1500-2500	4 FT	4.70	1.57	.105
68132	-	4 FT	6.70	2.30	.110

**Rolls**

68142	12-6	50 FT	.40	.15	.080
68144	8-1/0	25 FT	.75	.22	.080
68146	2-4/0	25 FT	1.10	.40	.080
68148	3/0-400	50 FT	1.50	.50	.080
68150	-	50 FT	1.70	.50	.080
68152	250-750	25 FT	2.05	.75	.080
68154	800-1250	25 FT	3.50	1.18	.095
68156	1500-2500	50 FT	4.70	1.57	.105
68158	-	25 FT	6.70	2.30	.110