

Photocontrols - Locking Style

LOCKING TYPE - SPEC GRADE



FIG 1



FIG 2



FIG 3

- Cost effective Means of Controlling Utility, Commercial & Residential Lighting Systems
- 30-120 Second Time Delay
- UV Stabilized Polycarbonate Cover and Clear Window
- High Impact Polybutylene Terephthalate Base
- IP65 Protection While Installed
- 1" Light Sensor
- Temp Rate: -40°F to 158°F
- Relative Humidity: 96%
- Power Consumption: 1.5 Watts Average
- Electrical Life: 6500 Cycles

MECHANICAL CONTACTS
NOT FOR USE WITH LED LIGHTING
SEE CAT PG 43 FOR LED PHOTOCELLS

CAT. NO.	FIG	VOLTAGE	TUNGSTEN RATING	BALLAST RATING	COLOR	CASE QTY
39053	1	120V	1800W	1000VA	GRAY	100
39051	2	208-277V	1800W	1000VA	MAROON	100

LOCKING TYPE - STANDARD



FIG 4



FIG 5

- Cost effective Means of Controlling Residential Lighting Systems
- 5-20 Second Time Delay
- UV Stabilized Polycarbonate Cover
- High Impact Polybutylene Terephthalate Base
- IP65 Protection While Installed
- 1/2" Light Sensor
- Temp Rate: -40°F to 158°F
- Relative Humidity: 96%
- Power Consumption: 1.5 Watts Average
- Electrical Life: 5000 Cycles



CAT. NO.	FIG	VOLTAGE	SURGE PROTECTION	TUNGSTEN RATING	BALLAST RATING	COLOR	CASE QTY
39050	4	120V	-	1800W	1000VA	CLEAR	100
39052	5	105 - 285V	235 JOULES/5,000A 820V CLAMPING	1000W	1800VA	BLUE	100

Photocontrols - Accessories



SHORTING CAP



- For testing twist-lock photocontrols while under maintenance
- UV Stabilized Polycarbonate Cover
- High Impact Polybutylene Terephthalate Base
- IP65 Protection While Installed

CAT. NO.	VOLTAGE	SURGE PROTECTION	TUNGSTEN RATING	BALLAST RATING	COLOR	CASE QTY
39056	480V	-	7200W	7200VA	BLACK	100
39058	480V	460 JOULES/10,000A 820V CLAMPING	7200W	7200VA	BLACK	100

OPEN CIRCUIT CAP



- Used for temporarily turning off a luminaire with twist lock
- UV Stabilized Polycarbonate Cover
- High Impact Polybutylene Terephthalate Base
- IP65 Protection While Installed

CAT. NO.	VOLTAGE	COLOR	CASE QTY
39057	480V	RED	100