

Photocontrols - Shutter Style



**FIXED
BASE**

- Polycarbonate Weatherproof Housing
- Adjustable Slide Bar Allows Field Adjustments
- 30-60 Second Time Delay
- Contact Position: Normally Closed
- SPST
- Temp Rate: -40°F to 158°F
- Relative Humidity: 96%
- Power Consumption: 1.5 Watts Average
- 6" Color Coded Leads
- 1/2" Threaded Base with Rubber Gasket & Zinc Locknut

FIXED BASE

CAT. NO.	VOLTAGE	TUNGSTEN RATING	BALLAST RATING	CASE QTY	EACH
39010	120V	2000W	2000VA	100	
39012	208-277V	2000W	2000VA	100	

SWIVEL BASE

CAT. NO.	VOLTAGE	TUNGSTEN RATING	BALLAST RATING	CASE QTY	EACH
39020	120V	2000W	2000VA	100	
39022	208-277V	2000W	2000VA	100	

MECHANICAL CONTACTS
NOT FOR USE WITH LED LIGHTING
SEE CAT PG 43 FOR LED PHOTOCELLS

Photocontrols - Shutter Style - Spec Grade



- Die Cast Aluminum Vandal Resistant Housing
- 1" Extra Wide Light Sensor for Increased Accuracy
- Adjustable Slide Bar Allows Field Adjustments
- 30-60 Second Time Delay
- Contact Position: Normally Closed
- SPST
- Temp Rate: -40°F to 158°F
- Relative Humidity: 96%
- Power Consumption: 1.5 Watts Average
- 6 Color Coded Leads
- 1/2" Threaded Base with Rubber Gasket & Zinc Locknut

FIXED BASE

CAT. NO.	VOLTAGE	TUNGSTEN RATING	BALLAST RATING	LIGHT SENSOR	CASE QTY	EACH
39011	120V	3000W	3000VA	1"	50	
39013	208-277V	3000W	3000VA	1"	50	

MECHANICAL CONTACTS
NOT FOR USE WITH LED LIGHTING
SEE CAT PG 43 FOR LED PHOTOCELLS

Locking Style Receptacles for Twist Lock Photoeye



FIG 1 - FIXTURE MOUNT

FIG 2 - BRACKET MOUNT

- Phenolic Socket
- Brass Contacts
- ABS Waterproof Back Cover
- 1/2" Conduit with Zinc Alloy Locknut
- Temp Rate: -40°F to 176°F
- Relative Humidity: 96%
- Voltage: 0-480V
- Amps: 15

CAT. NO.	FIG	DESCRIPTION	CASE QTY	EACH
39070	1	RECEPTACLE FIXTURE MOUNT	100	
39072	2	RECEPTACLE WITH ALUMINUM BRACKET MOUNT	100	