

# Photocontrols - Flush Mount



FIG 1

FIG 2

MECHANICAL CONTACTS  
NOT FOR USE WITH LED LIGHTING  
SEE CAT PG 43 FOR LED PHOTOCELLS

- Weatherproof Polycarbonate Housing & Lens
- SPST - Normally Open
- 1/2" CDS Photocell
- 30-60 Second Time Delay
- Light Levels: ON: .9 to 1.9 FC OFF: 2.8 To 5.6 FC
- Thermal Switch
- Temperature Range: -40°F to 158°F
- Relative Humidity: 98%
- Contact position at night is normally closed
- Power Consumption Below 1.5 Watts Max
- Life Cycle: 6500 Cycles
- 3/8" - 18 Thread Nipple with Rubber Gasket and Plastic Locknut
- 6" Leads Exit Rear of Housing for Tight locations
- 39069 body detached from sensor for convenient wiring

CAT. NO.	FIG	VOLTAGE	TUNGSTEN RATING	BALLAST RATING	CASE QTY	EACH
39030	1	120V	1800W	1100VA	150	
39032	1	208-277V	2000W	2000VA	150	
<b>MINI-FLUSH MOUNT</b>						
39069	2	120V	600W	480VA	150	

# Flush Mount with Wallplate



- Weatherproof Polycarbonate Housing & Lens
- Brushed Aluminum Wallplate and Gasket
- SPST - Normally Open
- 1/2" CDS Photocell
- 30-60 Second Time Delay
- Light Levels: ON: .9 to 1.9 FC OFF: 2.8 To 5.6 FC
- Thermal Switch
- Temperature Range: -40°F to 158°F
- Relative Humidity: 98%
- Contact position at night is normally closed
- Power Consumption Below 1.5 Watts Average
- Life Cycle: 6500 Cycles
- 3/8" - 18 Thread Nipple with Rubber Gasket Plastic Locknut
- 6" Leads Exit Rear of Housing for Tight locations

CAT. NO.	VOLTAGE	TUNGSTEN RATING	BALLAST RATING	CASE QTY	EACH
39040	120V	1800W	1100	100	
39042	208-277V	2000W	2000	100	

# Photocontrols - Pencil Type



SWIVEL BASE

MECHANICAL CONTACTS  
NOT FOR USE WITH LED LIGHTING  
SEE CAT PG 43 FOR LED PHOTOCELLS

- Weatherproof Polycarbonate Housing & Lens
- 1/2" CDS Light Sensor with Heat Sink
- Thermal Switch
- 30-60 Second Time Delay
- Light Levels: ON: .9 to 1.9 FC OFF: 2.8 To 5.6 FC
- Contact Position: Normally Open
- SPST
- Temperature Rate: -40°F to 158°F
- Relative Humidity: 98%
- Power Consumption: 1.5 Watts Max
- Life Cycle: 6500 Cycles
- 6" Color Coded Leads
- 1/2" Swivel Base Conduit with Rubber Gasket & Zinc Locknut

CAT. NO.	VOLTAGE	TUNGSTEN RATING	BALLAST RATING	CASE QTY	EACH
39060	120V	1800W	1100 VA	100	
39062	208-277V	1800W	1100 VA	100	

# Photocontrol Mount - Swivel Extender



- Swivel Adaptor for Photocontrol - Extends Length of Photoeye
- Works with any 1/2" NPT Stem Mount Photocell
- Polycarbonate

CAT. NO.	DESCRIPTION	BOX QTY	EACH
39063	PHOTOCONTROL MOUNT SWIVEL EXTENDER	1	