VIP-CAM-5-4K-USB2 4K USB 2.0 EPTZ Display Mounted Camera



The VIP-CAM-5-4K-USB2 4K display mounted camera features high-quality electronic pan, tilt, zoom mechanisms, high-performance optics, and a built-in microphone. With a USB 2.0 output, this plug and play camera is an excellent fit for broadcasting 4K video signals in conferencing, education, training webinars, online meetings, and many more applications.

Key Features

- 2160P 30Hz
- USB 2.0 output plug and play
- High-performance optics
- Electronic pan, tilt, zoom (EPTZ)
- Built-in microphone
- Computer monitor, laptop screen, TV/display mount

Technical Specifications

| IMAGE SENSOR | 1/2.5" Exmor CMOS, 8MP |
|-----------------------|------------------------|
| SUPPORTED RESOLUTIONS | up to 3840×2160@30fps |
| FOCAL LENGTH | 2.2mm |
| IRIS | F1.8 |
| FIELD OF VIEW | Horizontal 110 |
| MINIMUM ILLUMINATION | 1 Lux @ (F1.8, AGC ON) |
| AGC | Auto, Manual |
| WHITE BALANCE | Auto, Manual |
| EXPOSURE | Auto, Manual |
| S/N RATIO | ≥50dB |
| VIDEO COMPRESSION | MJPG/YUY2 |



VIP-CAM-5-4K-USB2 4K USB 2.0 EPTZ Display Mounted Camera

Interface

| VIDEO OUTPUT | USB 2.0 |
|-------------------|-----------|
| CONTROL INTERFACE | (1) USB |
| UVC PROTOCOL | UVC1.1 |
| UVC PTZ CONTROL | Supported |
| UAC | Supported |

General

| POWER SUPPLY | DC5V |
|-----------------------|----------------------------|
| POWER CONSUMPTION | < 2.5W |
| OPERATING TEMPERATURE | 0°C ~ 40°C |
| STORAGE TEMPERATURE | -20°C ~ 60°C |
| DIMENSION (LXWXH) | 208mm x 56mm x 48mm |
| WEIGHT | 0.22kg |
| WARRANTY | Limited Warranty (3-Years) |