

SOHO / Remote Office Cabinets

8U, 12U & 24U



Vericom® SOHO / Remote Office Cabinets are

Removable panel in top for

installation of optional fan unit for additional cooling

specifically designed for small offices and remote locations where space is a premium. Fully assembled and ready to deploy, they include all the features of a full-size server cabinet, conveniently sized to fit under or on top of a desk or counter. With a maximum rail depth of 29.5", these cabinets are capable of storing servers, networking switches, and a variety of other security and AV equipment, while high-flow vented doors provide passive cooling to keep equipment from overheating.



Side panels are lockable and removable for easy access to equipment



Vented front and rear doors swing open to 180 degrees and are lockable, removable and reversible



Top and bottom equipped with vents and cable access panels



Mounting rails, complete with 10-32 tapped holes and easy to read RU markings



Doors equipped with quick release hinge pins and ground wire

Benefits

Security & Protection

- Locking door and side panels prevent unauthorized access to equipment
- Two sets of rails provide a stable mounting structure
- Doors and side panels are grounded to the cabinet frame

Flexibility

- Includes both casters and adjustable leveling feet for both fixed and mobile installations
- Multiple cable entry slots provide greater flexibility during installation
- Mounting rails are adjustable in ³/₄" depth increments to match a variety of equipment sizes
- Front door, rear door and side panels are all removable for convenient access to equipment

High Capacity

- Available in three sizes to fit in a variety of environments where space is limited
- Deeper than a wall cabinet 29.5" maximum rail depth can handle servers and other large equipment
- Robust design can support 1,500 lbs
 of equipment

Key Features

- Sized to fit under a desk or counter
- Server depth
- · High-flow vented doors
- Locking doors and side panels

Engineered Solutions Made to Order for Tomorrow's Technology



Product Dimensions


| ltem Number | Product Dimensions (H x W x D) | Rack Unit Quantity | Maximum Rail Depth | Static Load Capacity |
|----------------|-----------------------------------|-----------------------|-----------------------|-------------------------|
| RSH0808 | 22 in. x 23.625 in. x 31.5 in. | 8U | 29.5 in. | 1,500 lbs. |
| RSH0812 | 29 in. x 23.625 in. x 31.5 in. | 12U | 29.5 in. | 1,500 lbs. |
| RSH0824 | 50 in. x 23.625 in. x 31.5 in. | 24U | 29.5 in. | 1,500 lbs. |


Optional Accessories


| ltem Number | Product Description | ltem Compatibility |
|----------------|----------------------------|---------------------------|
| RAFNQ04 | Top Mount Quad Fan | RSH0808, RSH0812, RSH0824 |
| RATSS01 | Solid Top Panel Insert | RSH0808, RSH0812, RSH0824 |
| RARSC08 | 8U Cage Hole Rails (4 Pk) | RSH0808 |
| RARSC12 | 12U Cage Hole Rails (4 Pk) | RSH0812 |
| RARSC24 | 24U Cage Hole Rails (4 Pk) | RSH0824 |

Additional accessories available. For a complete list visit vericomsolutions.com

Technical Illustration







Specifications

| Front and Rear Door | Removable, Reversible & Lockable High Flow Vented Steel, Opens Full 180° | | |
|----------------------------|--|--|--|
| Side Panels | Solid, Full Height, Removable & Lockable | | |
| Top Panel | (1) Vented Knockout for possibility of Optional Fan Unit | | |
| | (2) Removable Cable Entry Slots Located at Front and Back | | |
| Bottom Panel | (5) 2.75" Wide Individually Removable Covers (Maximum 11" x 15" Opening) | | |
| Bottom Faller | (2) Removable Cable Entry Slots Located at Front and Back | | |
| | Two Pairs of Mounting Rails | | |
| | Adjustable Depth Rails (5" - 29.5") | | |
| Equipment Support | 1.75" RU spacing, Marked and Numbered on Rails | | |
| Support | 19" W, EIA-310-D Universal Vertical Hole Spacing | | |
| | 10-32 Threaded Holes | | |
| Grounding | 14 AWG Ground Wire Connects Doors and Side Panels to Cabinet Frame | | |
| Finish | Black Powder Coat | | |
| Static Loading Capacity | 1,500 lbs. | | |
| Included Accessories | (4) Adjustable Leveling Feet(4) Casters(4) Grounding Kits(48) 10-32 Mounting Screws | | |
| Compliance | ANSI/EIA RS-310D IEC60297-2 DIN41494; Part 1 DIN41494; Part 7 | | |
| ANSI | | | |

TOP VIEW



10025 Investment Drive, Suite 120 Knoxville, TN 37932 USA

Engineered Solutions Made to Order for Tomorrow's Technology