



**WP9C006**

4 Fiber OM3 Breakout OFNR  
 Audio, Video and Data - Digital Video

**Construction & Dimenstions**

CONDUCTOR PARAMETERS	
Conductor Type	Optical Fiber
Number Of Fibers	4
Fiber Optic Size	50
OM Fiber Optic Rating	OM3
INSULATION PARAMETERS	
Insulation Type	Th rmoplastic
Buffer Size	900 m
Insulation Color Code	1.Blue,2.Orange,3.Green,4.Brown
SHIELDING PARAMETERS	
Fiber Optic Design	Breakout
ELECTRICAL CHARACTERISTICS	

**Overall Construction**

OVERALL CONSTRUCTION PARAMETERS	
Jacket Type	PVC
Nominal Cable O.D.	0.3 in
Plenum	No
NEC UL Rating	OFNR
RoHS Compliant	Yes
TIA Test	ANSI/TIA-568-C.3
Pull Tension	300 lbs
Bend Radius	3 in
Cable Weight	21 lbs

**Overall Electrical & Optical Characteristics**

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	
UL Flammability	UL1666 Vertical Shaft
CSA Flammability	FT6
Operating Range	-40 to 70 Deg C
Operating Wavelength	850/1300
Min. OFL Bandwidth	1500/500
Max. Attenuation	3.50/1.25