



WP9C241 T

Interlocked Armor Distribution Cable - 12 Fiber OM3 OFCP
 Audio, Video and Data

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	
CONDUCTOR PARAMETER	-
• Number Of Fibers	12
• Fiber Optic Size	50/125
• OM Fiber Optic Rating	OM3
INSULATION PARAMETER	-
• Insulation Type	Thermoplastic
• Buffer Size	900 m
• Insulation Color Code	1.Blue,2.Orange,3.Green,4.Brown,5.Slate,6.White,7.Red,8.Black,9.Yellow,10.Violet,11.Rose,12.Aqua
SHIELDING PARAMETER	-
• Fiber Optic Design	Indoor/Outdoor Plenum Direct Burial
• Armor Type	Interlocked Aluminum
• Flooding Compound	Yes

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	
Jacket Type	UV Resistant Polyolein
Nominal Cable O.D.	.506
Plenum	Yes
NEC UL Rating	OFCP
RoHS Compliant	Yes
TIA Test	TIA455-82 Water Penetration Test, MEETS ICEA S-104-696 TEST CRITERI (CORE CABLE ONLY)
Pull Tension	300 lbs
Bend Radius / Bend Radius Short Term	8 in / 11in
Cable Weight	103 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	
UL Flammability	NFPA 262
CSA Flammability	FT6
Operating Range	-40°C To +70°C
Operating Wavelength	850/1300 nm
Min. OFL Bandwidth	1500/500 MHz.km
Max. Attenuation	3.50/1.25 dB/km